

JOLUKA

Joluka Shutterboard Repair Epoxy Data Sheet

Product Description

Joluka Shutterboard Repair Epoxy is a solvent free epoxy adhesive used to repair wooden shutters where a quick set is required. Easy application with excellent adhesion to wooden shutters.

Application Areas

Rapid repairing defects on wooden shutterboards.

Typical Properties

Mixing Ratio:	2 : 1
Pot Life:	10 - 15 minutes
Set:	1-2 Hour at 25°C
Compression:	> 50 MPa
Application Temperature:	10°C to 35°C
Colour:	Black

Yield

Applied @1mm thick (1lt covers 1m²)

Packaging

Supplied in 2kg kits

Shelf Life:

One year in original unopened containers

Storage:

Store in a dry cool place

Placement Guidelines:

- Prepare the surface prior to application by removing all loose material, water, rust and any oil based products.
- The product consists of two parts; (PART A - Resin & PART B - Activator) (Ratio 2:1)
- Using a small trowel, mix 2 parts A and 1 part B. Mix the combined product thoroughly for at least 3-5 minutes.
- Apply the **Joluka Shutterboard Repair Epoxy** with a steel trowel onto the wooden shutters
- Clean equipment and brushes with an Epoxy Cleaner
- Mixing should not take place in temperatures below 5°C. Do not apply to wet surfaces.

Caution:

Avoid contact with eyes and skin. In case of contact with eyes, immediately flush eyes with water and immediately call a physician. Wash hands after contact. Always wear dust masks when handling, mixing and applying products. Also refer to **MATERIAL SAFETY DATA SHEET**.